

NON-SACRIFICIAL GRAF BARRIER COATINGS TECHNICAL DATA

Product Description:

A waterborne clear or pigmented coating to protect walls from permanent damage from graffiti. The product when applied to concrete, masonry, metal or wood dries to a hard, but flexible finish which protects the substrate from permanent graffiti made with spray paint or markers. The coating once cured does not allow graffiti to stick to its surface. The graffiti can be easily cleaned off with Graf Cleaner without affecting the barrier for years. The product can be used on vertical and horizontal surfaces.

Performance Features:

- . Coating can be produced in clear or pigmented versions with flat to gloss sheens
- . Coating developed to last years without having to re-coat surface
- . May be applied with brush, roller or spray
- . Low Odor & VOC compliant
- . Easy Application
- . Soap & hot water cleanup
- . Good for interior and exterior applications
- . Excellent Weather Resistance

Product Specifications for Clear:

Appearance: Colorless viscous liquid, dries transparent

Odor: Odorless

Density: 1.09 – 1.13 g/ml

Specific Gravity: 1.09 – 1.13

Boiling Point: 100 degrees C <

Viscosity (25 deg C) : 200 mPa.s (estimated)

Solubility in water: Miscible

Numbers Represent Values For Combined Part A and B

Solids by Weight: 34.37%

Solids by Volume: 39.77%

Shelf Life: Typical Shelf Life is Two Years

VOC: 98.22 Grams Per Liter

Pot Life After Mixing: 75 Minutes Prox.

Clean Up: Hot Soapy Water

Page Two

Dry Time 78 F @ 50% RH

TO TOUCH: One Hour

DRY HARD: Six Hours

COVERAGE: AT 3 Mils Dry 181 Square Feet Per Gallon

SHIPPING: Product is not regulated and is shipped as class 55 on commercial freight carriers

APPLICATION: Product may be applied by roll, brush, or conventional or airless spray. Spray tip size will vary based on surface to be coated and how thick the coating is to be applied. This same rule follows with pressure to be used, although tests have been run with commercial air assisted pressure pots successfully. To roll the product a short knap roller is recommended.

LIMITATION OF LIABILITY To the best of our knowledge the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specifications contained herein. **WE MAKE NO WARRANTY OR GUARANTEE OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING MERCHANTABILITY AND FITNESS FOR PARTICULAR PURPOSE.** Liability, if any is limited to replacement of the product or refund of the purchase price at our discretion. **LABOR OR COST OF LABOR AND RESULTING CONSEQUENTIAL DAMAGES ARE HEREBY EXCLUDED.**